



## *Laser 115.6 Turbo*

### **Reliable in all condition.**

A high confort level and engines capable of delivering the power required to operate in all tranquility with maximum reliability and minimizing operating costs. A tractor designed to provide maximum performance with 6 cylinders engine Tier2 Turbo and electronic control, with maximum transmission speed of 40 km/h and with a spacious cabin with ergonomic and functional a high visibility roof.

LASER  
TURBO:  
115.6



**SAME**

ENGINE		
Emissions		Tier2
Manufacturer		SDF 1000.6 WT
Cylinders/Capacity	n°/cm³	6/6000
Turbocharged intake		●
Max. power	kW/HP	85/115.6
Max. engine speed (rated)	rpm	2350
Max. torque	Nm	477.5
Max. torque engine speed	rpm	1400
Electronic engine control		●
Cyclone pre-filter		●
Cooling liquid		●
Under-hood silencer with side exhaust		○
Fuel tank capacity	liters	180
MECHANICAL GEARBOX		
Synchronised		●
Electrohydraulic engagement differential lock		●
Number of speeds	n°	15+15
Number of speeds with creeper	n°	20+20
Minimum speed/Minimum speed with creeper	km/h	1.78/0.52
Maximum speed	km/h	40
Hydrostatically operate self-adjusting dry clutch, single		●
REAR PTO		
Electrohydraulic clutch with multiple discs		●
540/1000	rpm	●
FRONT AND REAR AXLE		
Fixed front axle		●
Steering angle	degrees	50
BRAKES		
Hydrostatically operated brakes		●
Oil immersed disc brakes		●
Mechanical parking brake		●
Brakes on 4 wheels		●
STEERING		
Hydrostatically steering with independent pump		●
HITCH		
Category		II
Mechanical rear hitch		●
Maximum lift capacity	kg	6200
HYDRAULIC SYSTEM		
Pump output (std)	l/min	58
Open centre hydraulic system		●
Mechanical distributor engagement		●
Rear auxiliary distributors	n°	3
DRIVING POSITION		
Side control levers		●
Driver seat with mechanical suspension		●
Cab or Flat platform		●
DIMENSIONS AND WEIGHTS		
Standard rear tyres		460/85R34 (18.4 R 34)
Standard front tyres		420/85R24 (16.9 R 24)
Length	mm	4108
Width (min.-max.)	mm	2082-2304
Height	mm	2687
Wheelbase	mm	2633
Front track (min.-max.)	mm	1728-2128
Rear track (min.-max.)	mm	1702-2102
Ground clearance	mm	475
Total unladen weight	kg	4320

- STD
- Not available

DEALER

To discover more please contact your dealer  
or visit [same-tractors.com](http://same-tractors.com)

SAME is a brand of  SDF

