

## Tiger COMPACT

## Simplicity is the main feature.

Easy to drive, easy to maintain and simple in design. Tiger Compact tractors are versatile range with the size and the right weight for different agricultural jobs: from livestock farm to work in the open field or in specialised crops (horticulture, orchards, vineyards and parks). In fact, it is compact, maneuverable and it is able to work in all conditions.

TIGER COMPACT: 35E | 40E | 42E



Tiger con		35 E	40 E	42 E
ENGINE				
Emissions		Bharat Trem 3A	Bharat Trem 3A	Bharat Trem 3A
Manufacturer		\$324	\$325.1	\$325.1
ylinders/Displacement	n°/cm³	3/2400	3/2500	3/2500
laturally aspirated		•	•	•
lax power	kW/HP	28.6/36	31.3/42	31.3/42
ated power	rpm	2000	2000	2000
lax torque	Nm	137.4	165.8	165.8
ngine control mechanical		•	•	•
ooling system		•	•	•
lencer with vertical exhaust		•	•	•
uel tank capacity	liters	55	55	55
ECHANICAL GEARBOX				•
nchronised		•	•	•
fferential lock			-	Mechanically operated
umber of speeds	n°	8+2	8+2	8+2
in speed	km/h	2.61	2.6	2.6
ax speed	km/h	32	32	32
echanical clutch dry, single		•	•	•
EAR PTO				
lechanical clutch dry, single		•	•	•
TO 540		•	•	•
RONT AND REAR AXLE				
xed front axle		•	•	•
eering angle	degrees	50°	50°	50°
RAKES	uegrees	30	30	30
lechanically operated		•	•	•
il immersed disc brake		•	•	•
		•	•	•
lechanical parking brake		<u> </u>	•	•
reering				
lechanical steering		•	•	•
TCH .				
ategory		II .	II	II
ear hitch mechanical		4250	4350	4250
ear lift capacity	kg	1250	1250	1250
asy lift		•	•	•
YDRAULIC SYSTEM				
ump output (std)	l/min	24	24	24
pen centre hydraulic system		•	•	•
pping system		•	•	•
RIVING POSITION				
de control levers		•	•	•
xed opeator seat		•	•	•
MENSIONS AND WEIGHTS				
andard rear tyres		12.4-28"	12.4-28"	13.6-28"
ength	mm	3220	3220	3220
/idth	mm	1600	1600	1600
eight	mm	2185	2185	2195
/heelbase	mm	1800	1800	1800
ont track	mm	1260	1260	1260
ear track	mm	1300	1300	1330
round clearance	mm	400	400	410
/eight	kg	1620	1620	1660

• STD

- Not available

DEALER

To discover more please contact your dealer or visit **same-tractors.com** 

