

[CODENAME]

TIGER COMPACT

[DISTINGUISHING FEATURES]

VERSATILE AND RELIABLE.



The new Tiger Compact 46/60 features a modern driver area designed in accordance with the latest standards for ergonomics. Conceived specifically for emerging countries, the range consists of 4 models with power outputs from 45 to 60 HP and with 2 or 4 wheel drive. These machines are built tough but with contemporary, attractive looks. With their sturdy construction, tried-and-tested engines and transmissions and high performance hydraulic rear lifts, these tractors can work effectively with many implements that would normally only be usable with much bigger, more powerful tractors.

TIGER COMPACT: 46 / 50 / 55 / 60



SAME


TIGER COMPACT

TECHNICAL DATA

		45	50	55	60
ENGINE					
Emissions		Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		Simpson	SDF	SDF	SDF
Cylinders/Capacity	n°/cc	3/2700	3/3000	3/3000	3/3000
Aspiration		Natural	Natural	Turbo Intercooler	Turbo Intercooler
Max. & Rated power (ECE R120)	kW/HP	33/45	36.8/50	40.4/55	44.1/60
Rated engine speed	rpm	2200	2200	2200	2200
Max. torque	Nm	180	184	201	221
Mechanical engine control		▲	▲	▲	▲
Cooling liquid		▲	▲	▲	▲
Under-hood silencer with vertical exhaust		▲	▲	▲	▲
Fuel tank capacity	litres	55	55	55	55
TRANSMISSION 1					
Synchronised		○	○	○	○
Number of speed (with creeper)	n°	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		▲	▲	▲	▲
Waterproof seals		▲	▲	▲	▲
TRANSMISSION 2					
Synchronised		▲	▲	▲	▲
Number of speed (with creeper)	n°	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		▲	▲	▲	▲
Waterproof seals		▲	▲	▲	▲
REAR PTO					
Mechanical dry clutch		▲	▲	▲	▲
Mechanical engagement		▲	▲	▲	▲
PTO 540 / 540-540E / 540-1000		▲ / ○ / ○	▲ / ○ / ○	▲ / ○ / ○	▲ / ○ / ○
PTO 540 + reverse PTO		○	○	○	○
FRONT AND REAR AXLE					
Front wheel drive mechanically engaged (only 4WD)		▲	▲	▲	▲
Mechanically operated differential lock (rear/front)		▲/-	▲/-	▲/-	▲/-
Steering angle (2WD/4WD)	degrees	55/51	55/51	55/51	55/51
BRAKES					
Girling braking system		▲	▲	▲	▲
Mechanical parking brake		▲	▲	▲	▲
STEERING					
Hydrostatic steering with independent pump		▲	▲	▲	▲
HITCH					
Category		II	II	II	II
Mechanical rear hitch with Easy Lift system		▲	▲	▲	▲
Rear hitch lift capacity	kg	1250	1600	1600	1600
HYDRAULIC SYSTEM					
Pump output (std)	l/min	27	31	31	31
Rear hydraulic auxiliary valves	n° of ways	2/4	2/4	2/4	2/4
DRIVING POSITION					
Side control levers		▲	▲	▲	▲
2 post ROPS		○	○	○	○
Driver seat with mechanical suspension		○	○	○	○
DIMENSIONS AND WEIGHTS					
Rear tyres		16.9-28"	16.9-28"	16.9-28"	16.9-28"
Max. length	mm	3550	3550	3550	3550
Width (min.-max.)	mm	1800-1840	1800-1840	1800-1840	1800-1840
Wheelbase (4WD/2WD)	mm	1950/1920	1950/1920	1950/1920	1950/1920
Front track (4WD/2WD)	mm	1488/1462	1488/1462	1488/1462	1488/1462
Rear track	mm	1440	1440	1440	1440
Max. height at steering	mm	1634	1634	1634	1634
Weight with ROPS (4WD/2WD)	kg	2500/2100	2500/2100	2500/2100	2500/2100

▲ STD ○ OPT - Not available

Area dealer



To find out more, visit same-tractors.com or talk to you dealer.



SAME is a brand of SDF

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice. 308.8702:3.1-0 - 07/20-



SAME