

[CODENAME]

DORADO NATURAL

STAGE V

70 | 80 | 90 | 100



MISSION

NATURALLY A WINNER.

As simple to use as it is rich in technological content, the SAME Dorado Natural stands out for its great versatility too, working in the best possible way both in the open field and in limited spaces (i.e. greenhouses, stables).

The new FARMotion 35 engines, together with optimum comfort and a wide choice of configurations are characteristics that make the SAME Dorado Natural the ideal tractor for winning every match. The new cab provides a modern, comfortable and ergonomic work environment, and the new transmissions not only ensure the right pace out in the field but are also designed to travel at 40 km/h on the road with the engine running in economy mode.

The SAME Dorado Natural range offers models that boast excellent manoeuvrability, to move easily in even the narrowest spaces, and a torque supply that's ideal for the agricultural context. At the same time, the tried and tested 5-speed transmissions - completed with modern electro hydraulic engagement for front wheel drive and differential tocking guarantee excellent traction and robustness, allowing even the hardest field work to be easily carried out.






JÖRN FOR AGRICULTURE.

An engine conceived for farming. In day to day use, the difference this makes is clear!

The Dorado Natural range comprises 4 models from 66 to 102 HP, powered by advanced 3-cylinder FARMotion 35 engines that not only offer compactness and proven reliability but also efficiency maintenance and minimal needs. The innovative FARMotion 35 engine is purposely designed, in fact, for agricultural use; the 3-cylinder version is fitted on the SAME Dorado Natural, to enhance the already excellent handling of these machines. The use of a viscostatic fan, turbocharger with Intercooler and waste-gate valve, along with a Common Rail injection system up to 2,000 bar and the latest 7-hole piezoelectric injectors (for optimum diesel spraying to ensure efficient combustion), produces first class results whilst at the same time keeping diesel consumption at the lowest levels in this category. Furthermore, the FARMotion



35 engines offer almost constant power supply over a wide speed range and with high torque, even at low rotation speeds. The advanced conception and innovative technical solutions ensure that FARMotion 35 engines comply with the limits envisaged by Stage V in terms of polluting emissions, merely using the DOC+DPF (for the models 70 and 80) or DOC+DPF+SCR (for the models 90-100). FARMotion 35 engines are distinguished by their outstanding performance figures: the maximum rotation speed is only 2,200 rpm; the version installed on the SAME Dorado 100 Natural provides a torque reserve of 35% and it develops a maximum torque of 417 Nm." Apart" from optimising "consumption", the fully electronic diesel injection control also allows two work speeds to be memorised. These are directly activated from the driver's seat by means of a dedicated button command, leaving the ECU with the task of proportioning fuel use on the basis of the load. This means the connected attachments can be used in a smooth manner, even with the sudden load variations that are a typical feature of many types of agricultural work. The new layout underneath the bonnet offers a sheltered, protected area for both the DOC catalytic converter and the new PowerCore 2-stage air filter which can be fitted upon request with a dust ejector). Two practical sliding screens have been added, to protect the radiator pack and facilitate maintenance.

70: 66 HP / 48.9 kW

80: . 76.HP / .55.8 kW


-90: - 91 HP / -67-kW

100: 102 HP / -75 kW



TRANSMISSION, PTO AND HYDRAULICS

THE TOP IN TERMS OF VERSATILITY AND SAFETY.



A wide choice of transmission configurations further increases the versatility of the Dorado Natural. The standard one offers 5 speeds for 3 ranges, with the shortest gear ratio enabling the tractor to move forward at 298 m/h (with the engine at maximum speed). With the optional splitter (activated by means of a handy lever just beneath the steering wheel), the forward gear ratios are doubled (producing a combination of 30+15) and the shortest gear ratio enables movements of just 245 m/h (with the engine running at maximum speed). To further boost productivity and comfort levels, PowerShuttle and Hi-Lo 2-steps Powershift are even available. All Dorado Natural equipped with PowerShuttle offers as standard an exclusive pack of features such as Stop&Go, ComfortClutch and SenseClutch. Stop&Go is the function which allows to stop and restart the tractor using only brake pedals. ComfortClutch is the function which duplicates the clutch control on gear knob and SenseClutch allows the driver to adjust the PowerShuttle responsiveness in 5-levels. All transmissions allow to travel at 40 km/h with the engine running at just 1800 rpm, which means significant fuel savings during fast movement on the road. The front axle, entirely designed and built by SAME, has a maximum steering angle of 55°, with a maximum permitted load of 2300 Kg, and the front wheels are fitted with brake discs for absolute safetu.



PTO AND HYDRAULICS

The PTO comes as standard with 540 rpm and 540ECO speed modes, but a 1000 rpm mode or groundspeed PTO can also be added as an option.

The Dorado Natural can also be successfully coupled with very demanding hydraulic equipment: the models in the range are in fact equipped with a 56 l/min pump dedicated to the rear linkage and auxiliary 4-coupler distributors (6 couplers as an option) with classic mechanical control. The steering circuit is served by an additional independent 20 I/ min pump for maximum safety and smooth driving even when the engine is at minimum speed. The rear linkage has a maximum capacity of 2500 Kg close to the ball joints, increased to 3500 Kg with the additional optional culinders. For rear lift control is now available the EasyLift system that allows to raise and lower the implements using a single button on the console.

The ideal front loader tractor

Dorado Natural can also be pre-arranged for front loader applications thanks to the







DRIVING POSITION

TOP CLASS COMPORT.

The driving seat of the new SAME Dorado Natural range guarantees a high level of comfort, usually found only on high-power tractors. The new layout is perfect in every way, and the well-established SAME colour logic for the commands make even the most complex tasks quick and easy.

The new Dorado Natural cab is the result of a thorough design study to obtain first-rate comfort: the platform is suspended on special Silent-Blocks, which effectively dampen the transmission vibration. The driver's seat is equipped with efficient mechanical suspension with adjustable rigidity, adapting to the driver's weight whilst still ensuring excellent vibration mitigation. For those aiming for even greater comfort, the optional configurations include a seat with pneumatic suspension.

The new command layout is designed to be rational, highly responsive and user-friendly. The analogue/digital display follows the steering column in the correct adjustment of the till, thus ensuring a clear view of the machine's main operating parameters at all times. The new Dorado Natural can also be fitted with an optional high-visibility panoramic roof, or a type-approved FOPS roof for protection against objects that accidentally fall from above.



DORADO NATURAL

						1
Madel			70	80	90	100
Single S						
Cylindare/Displacement						
Bons		0.4				
Application Dispetation						
Injection Purpose Pu		mm				
Max. pawer il 2.000 pm	·	Tune				
Rede opener 2,200 cm			/18 9/66			75/102
Max. Incrue Nn 237 8 1900 348 1900 376 1900 477 9 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900 100 1900						
Toque rise						
First InstAudPulse	Torque rise					
EAT	Visco cooling fan		A	A	A	A
TRANSMISSION Type	Fuel tank/AdBlue	I	90/- 90/2			
SDF Intermission Tupe T3300 1383		System	DOC ·	+ DPF	DOC + 1	DPF + SCR
Tansension rate METANICA SHUTTLE						
MCFFANCAL SENTITLE		Туре				
Gearbox				1.3	83	
N° 15-95 N° N° N° N° N° N° N° N		0		_		
N° of speed with mechanical spiller						
Top speed 4D km/h EED rpm 1800 ► POWRERH-TUTE FOR Seption X n° \$ 18-15 N° of speed with 2 Powershift steps n° \$ 18-15 N° of speed with 2 Powershift steps n° \$ 30-30 Stops650 . . SenseCluth . . ComfortDutch . . Top speed 4D km/h EED rpm 1800 ► BTO . . \$40,540ECO . . \$50,940ECO . . \$40,950ECO						
Profestional Content						
Searbox		Mcli		181	, or	
N° of speed with 2 Powershift steps n° 30+30 Sitopticia		n°		5 nears v	3 rannes	
N° disped with 2 Powershit sleps n° 30+30 SistopEGo SenseEUtch A ComfortDutch Top speed 40 km/h ECO ym 1800+ PTO SAD SADECO A SAD SADECO B Webhanical rear lift Mechanical rear lift with "EASYLIFT" A Mechanical rear lift with "EASYLIFT" A Rear lifting capacity (PTI) Kg 2500 Rear lifting capacity (PTI) Kg 3500 HYDPAULUS HYDPAULUS HYDPAULUS HYDPAULUS HYDPAULUS A Wheel blaking A Mechanical parking brake Hydraulic DualMode traiter brake A Wheel Daking angle Electhopyldraulic UND engagement Electhopyldraulic UND engagement Electhopyldraulic Dial Lock engagement CAS Adjustable steering column A Openable front and rear windows Pneumalic seal suspension A Menual AC Hydr Storing AND Welfelts With rear tyre Size 42070 R30" Wheelbase mm 2000 Max. length mm 2820 Weight mm 2820 Weight Weight Min mm 1820 Fool Hydr Storing AND Welfelt mm 2820 Weight Weight Min mm 1820 Fool Hydr Storing AND Welfelt mm 2820	N° of speed					
Stoption						
CombortUlateh	Stop&Go					
Top speed 40 km/h ECO rpm 1800 • \$400 540 ECO • • \$400 540 ECO O • Ground speed PTO • • LEF — • Mechanical rear liff • • Mechanical rear liff wilh "EASYLIFT" • • Rear lifting capacity (19T0) Kg 3500 Rear lifting capacity (19T1) Kg 3500 HY0 RAULICS — — Pump flow (5TD) I/min 48 Pump flow (19T1) I/min 55 Rear spool valves n° 2/3 PEARES 4 — 4 wheel braking • • Mechanical parking brake • • 4 wheel braking brake • • 4 wheel	SenseClutch		A			
### ADD STANDER OF THE PROPOSED OF THE PROPOSE	ComfortClutch		A			
\$400540ECO	Top speed 40 km/h ECO	rpm	1800∗			
\$40/\$40ECO/1000 \$510/\$40ECO + Groundspeed PTO	PTO					
SADISADECO + Groundspeed PTO	540/540ECO		A			
Mechanical rear life	540/540ECO/1000					
Mechanical rear lift • Mechanical rear lift with "EASYLIFT" • Rear lifting capacity (STD) Kg 2500 Rear lifting capacity (OPT) Kg 3500 HYORAULICS ************************************			0			
Mechanical rear liff with "EASYLIFT" O Rear lifting capacity (IDPT) Kg 3500 HYDRAULICS 3500 Pump flow (STD) I/min 48 Pump flow (DPT) I/min 56 Rear spool valves n° 2/3 BRAKES 4 4 wheel braking • • Mechanical parking brake • • Hydraulic DualMode trailer brake • • MVDERDINI AXLE ** ** Front axle Size 1 ** Sleering angle degrees 55 ** Electrohydraulic IVMD engagement • • ** CAB ** ** ** Adjustable steering column • • ** Openable front and rear windows • • ** Pneumalic seat suspension • • ** Manual AC • • ** High visibility roof • • ** <						
Rear lifting capacity (STD) Kg 2500 Rear lifting capacity (DTT) Kg 3500 HYDRAULUS 3500 Pump flow (STD) I/min 4B Pump flow (DTT) I/min 56 Rear spool valves 67 2/3 BRAKES						
Rear lifting capacity (OPT) Kg 3500 HYDRAULICS HYDRAULICS Pump flow (STD) Vmin 4B Pump flow (OPT) Vmin 56 Rear spool valves n° 2/3 BEAKES BEACKES CA 4 wheel braking A A Mechanical parking brake A A Hydraulic Dualkhode trailer brake O A 4 Wheel Braking A A Hydraulic Dualkhode trailer brake O A 4 Wheel Braking A A 4 Wheel Braking A A 4 Wheel Braking A A 4 Will Frank AVE Size 1 5 Steering angle degrees 55 6 Lectrohydraulic AWD engagement A C CAB A C Adjustable steering column A C Openable front and rear windows A C Pneumalic sea! suspension A C Manual AC		Ка				
HYDRAULICS Vimin 48 Pump flow (STD) Vimin 55 SE SE SE SE SE SE SE						
Pump flow (DPT) I/min 56 Rear spool valves n° 2/3 BEAKES P 4 wheel braking	HYDRAULICS					
Rear spool valves n° 2/3 ERAKES Common of the problem of the	Pump flow (STD)	l/min	48			
BRAKES A 4 wheel braking A Mechanical parking brake A Hydraulic DualMode trailer brake o 4WD FRONT AXLE Size Front axle Size 1 Steering angle degrees 55 Electrohydraulic WID engagement A 6 Electrohydraulic Diff Lock engagement A 6 CAB A 6 Adjustable steering column A 6 Openable front and rear windows A 6 Pneumatic seat suspension O 6 Manual A/C O 6 High visibility roof O 6 FDP5 certification O 6 DIMENSIONS AND WEIGHTS Size 42070 R30" With rear tyre Size 42070 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axie - Cab mm 1820 Total height mm 1892 Width <td>Pump flow (OPT)</td> <td>l/min</td> <td colspan="4">56</td>	Pump flow (OPT)	l/min	56			
4 wheel braking A Mechanical parking brake A Hydraulic DualMode trailer brake O 4WD FRONT AXLE Size Front axle Size 1 Sleering angle degrees 55 Electrohydraulic VWD engagement A Electrohydraulic Diff Lock engagement Electrohydraulic Diff Lock engagement A Electrohydraulic Diff Lock engagement AGJustable steering column A A Openable front and rear windows A A Pneumalic seat suspension A A Manual A/C O A High visibility roof O O FOPS certification O O DIMENSIONS AND WEIGHTS VIII rear tyre Size 42070 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Width mm 2520 Width mm 1882 Weight Kg 3250 <td></td> <td>n°</td> <td colspan="4">2/3</td>		n°	2/3			
Mechanical parking brake A Hydraulic DualMode trailer brake O WID FRONT AXLE C Front axle Size 1 Steering angle degrees 55 Electrohydraulic 4WD engagement A C Electrohydraulic Diff Lock engagement A C CAB C C Adjustable steering column A C Openable front and rear windows A C Pneumatic seaf suspension O C Manual A/C O C High visibility roof O C FDPS certification O C DIMENSIONS AND WEIGHTS O C With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1880 Width mm 2520 Width mm 1882 Weight Kg 3250						
Hydraulic DualMode trailer brake #### FRONT AXLE Front axle Size Siz	-					
AWD FRONT AXLE Size 1 Front axle Size 1 Steering angle degrees 55 Electrohydraulic AWD engagement • • Electrohydraulic Diff Lock engagement • • Electrohydraulic Diff Lock engagement • • Adjustable steering column • • Openable front and rear windows • • Pneumatic seat suspension • • Manual A/C • • High visibility roof • • FOPS certification • • OIMENSIONS AND WEIGHTS • • With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250	Mechanical parking brake					
Front axle Size 1 Steering angle degrees 55 Electrohydraulic AWD engagement A A Electrohydraulic Dilf Lock engagement A A Electrohydraulic Dilf Lock engagement A A CAB B B Adjustable steering column A A Openable front and rear windows A A Pneumatic seat suspension A A Manual AC O A High visibility roof O O FDPS certification O O DIMENSIONS AND WEIGHTS B B With rear tyre Size 420/70 R30" Wheelbase mm B990 Centre rear axle - Cab mm B890 Centre rear axle - Cab mm B82 Width mm B882 Weight Kg 3250			0			
Steering angle degrees 55 Electrohydraulic AWD engagement . . Electrohydraulic Diff Lock engagement . . EAB ***********************************		C:			1	
Electrohydraulic AWD engagement Electrohydraulic Diff Lock engagement Adjustable steering column Adjustable front and rear windows Pneumatic seat suspension Annual A/C High visibility roof FOPS certification OBIMENSIONS AND WEIGHTS With rear tyre Wheelbase Max. length Max. length Centre rear axle - Cab Max Width Mm Max Wight Mm Max Beac Weight Msg W						
Electrohydraulic Diff Lock engagement CAB Adjustable steering column Openable front and rear windows Pneumatic seat suspension Manual A/C High visibility roof FOPS certification OMENSIONS AND WEIGHTS With rear tyre Wheelbase Mm AB90 Centre rear axle - Cab mm Dies in the steer		uegrees				
CAB Adjustable steering column ▲ Openable front and rear windows ▲ Pneumatic seat suspension ○ Manual A/C ○ High visibility roof ○ FOPS certification ○ DIMENSIONS AND WEIGHTS With rear tyre Size Wheelbase mm Max. length mm Centre rear axle - Cab mm Total height mm Width mm 1882 Weight Kg 3250						
Adjustable steering column Openable front and rear windows Pneumalic seat suspension Manual A/C High visibility roof FOPS certification OIMENSIONS AND WEIGHTS With rear tyre Size Wheelbase mm Size 420/70 R30" Wheelbase mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250						
Openable front and rear windows ▲ Pneumatic seat suspension ○ Manual A/C ○ High visibility roof ○ FOPS certification ○ DIMENSIONS AND WEIGHTS ■ With rear tyre Size 420/70 R30" Wheelbase mm ≥100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250						
Pneumatic seat suspension O Manual A/C O High visibility roof O FOPS certification O DIMENSIONS AND WEIGHTS Size With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250						
Manual A/C 0 High visibility roof 0 FOPS certification 0 DIMENSIONS AND WEIGHTS 0 With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250	•					
FOPS certification O DIMENSIONS AND WEIGHTS Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250	Manual A/C		0			
DIMENSIONS AND WEIGHTS Size 420/70 R30" With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250	High visibility roof		0			
With rear tyre Size 420/70 R30" Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250					0	
Wheelbase mm 2100 Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250	DIMENSIONS AND WEIGHTS					
Max. length mm 3890 Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250		Size				
Centre rear axle - Cab mm 1820 Total height mm 2520 Width mm 1882 Weight Kg 3250						
Total height mm 2520 Width mm 1882 Weight Kg 3250	-					
Width mm 1882 Weight Kg 3250						
Weight Kg 3250	-					
IUI OI OUIIII DOU DE LI DO	-					
	וטופו סטווווכבווטפ	ny	JEUU			

^{*}with 480/70 R30 rear tyres

[▲] STD

O OPT - Not available

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.

Cod. 308.8956.3.1-1 - 07/23

SAME

To find out more, visit **same-tractors.com** or talk to your dealer.



SAME is a brand of SDF