



SAME *55-60*

Essential and well controlled.

SAME machines are ideal for medium power applications, even in the most challenging conditions. The tried and tested SDF 1000.3 engine ensures high productivity. It offers up to 60 hp of mechanical transmission with 4 speeds and 2 ranges. The SAME range is compact, versatile and easy-to-use.



SAME		55	60
ENGINE			
Emissions		Tier1	Tier1
Manufacturer		SDF 1000.3	SDF 1000.3
Cylinders/Capacity	No./cm ³	3/3000	3/3000
Natural aspiration		•	•
Max. homologated power (ECE R-120)	kW/HP	37/50	44/60
Max. engine speed (rated)	rpm	2350	2350
Max. torque	Nm	175	185
Mechanical engine control		•	•
Cyclone prefilter		•	•
Cooling liquid		•	•
Under-hood silencer with vertical exhaust		•	•
Fuel tank capacity	litres	56	56
MECHANICAL GEARBOX			
Synchronised		•	•
Number of speeds	n°	8+2	8+2
Number of speeds with reduction gear	n°	12+3	12+3
Minimum/maximum speed with reduction gear	km/h	0.81/2.91	0.83/2.95
Max. speed	km/h	30	30
Mechanical dry clutch, single		•	•
REAR PTO			
Mechanical dry clutch, single		•	•
Mechanical engagement		•	•
PTO 540		•	•
FRONT AND REAR AXLE			
Front wheel drive mechanically engaged (for 4WD versions only)		•	•
Mechanically operated differential lock		•	•
Steering angle/turning circle 2WD	degrees/mm	50°/3550	50°/3550
Steering angle/turning circle 4WD	degrees/mm	55°/3700	55°/3700
BRAKES			
Braking system with wet brake discs		•	•
Mechanical parking brake		•	•
STEERING			
Hydrostatic steering with independent pump		•	•
HITCH			
Category		II	II
Mechanical rear hitch		•	•
Rear hitch lift capacity	kg	1500	1500
HYDRAULIC SYSTEM			
Pump output (std)	l/min	31	31
Open-centre hydraulic system		•	•
Mechanical distributor engagement		•	•
Rear hydraulic auxiliary valves	No. of ways	2/4	2/4
DRIVING POSITION			
Side control levers		•	•
ROPS with two uprights		○	○
Driver seat with mechanical suspension		•	•
Analogue instrumentation		•	•
DIMENSIONS AND WEIGHTS			
Standard rear tyres		14.9R28"	16.9R28"
Max. length	mm	3202	3225
Width (min-max)	mm	1685/2125	1822/2336
Wheelbase (4WD/2WD)	mm	1975/2045	1975/2045
Front track (4WD/2WD)	mm	1455/1250	1480/1335
Rear track	mm	1340	1410
Max height at steering	mm	1505	1505
Max. height at cowl	mm	1355	1355
Weight with ROPS (4WD/2WD)	kg	2150/1940	2300/2090

• STD ○ OPT

Dealer

same-tractors.com

Use of original SDF lubricants and coolants is recommended.

SAME is a brand of  SDF

