



## Go-anywhere capability in total safety.

The SAME Krypton crawler is the most powerful model in the family, ready to tackle any terrain and cater for the typical needs of specialised farming. Created to deliver unparalleled performance in the challenging conditions of hilly or mountainous terrain. With a modern design with soft, rounded forms conceived for excellent visibility and to minimise crop damage, the Krypton boasts a wheelbase of 1850 mm and an innovative 6-roller undercarriage offering even greater stability and traction. KRYPTON: 115





|     | _ |          |
|-----|---|----------|
| Kry |   | $\frown$ |
|     |   |          |

|   |             | 115               |
|---|-------------|-------------------|
| ENGINE  |             |                   |
| Model   |             | FARMotion         |
| Emissions compliance  |             | Stage III B       |
| Manufacturer  |             | SDF               |
| Cylinders/capacity  | No./cc      | 4/3.849           |
| Induction   |             | Turbo intercooler |
| Injection   |             | Common Rail       |
| Maximum power at 2.000 rpm                                      | kW/HP       | 83/113            |
| Rated power @ 2.200 rpm   | kW/HP       | 79/107            |
| Max. torque @ 1600 rpm  | Nm          | 435               |
| Torque rise   | %           | 28                |
| Viscostatic cooling fan   |             | •                 |
| 8" air filter with dust ejector (PowerCore)                     |             | •                 |
| Fuel tank capacity  | Litres      | 130               |
| SHUTTLE   |             |                   |
| Synchronised mechanical reverse shuttle                         |             | •                 |
| 4-SPEED MECHANICAL GEARBOX                                      |             |                   |
| Number of speeds with supercreeper gear                         | No.         | 12+12             |
| Minmax. speeds with supercreeper gear                           | km/h        | 0,38-10,5         |
| Number of speeds with OverDrive                                 | No.         | 16+16             |
| Minmax. speeds with overdrive                                   | km/h        | 1,32-12,5         |
| REAR PTO  |             |                   |
| Multiplate wet clutch   |             | •                 |
| PTO 540/540ECO - 540/1000                                       |             | ●/○               |
| BRAKES AND STEERING   |             |                   |
| Multi-plate wet lateral steering clutches                       |             | •                 |
| Wet band steering brakes  |             | •                 |
| Pedal operated service brake                                    |             | •                 |
| LIFT  |             |                   |
| Mechanically controlled rear lift                               |             | •                 |
| Rear lift capacity  | kg          | 3170              |
| Fixed / auto-hitch link arms                                    |             | ●/○               |
| HYDRAULIC SYSTEM  |             |                   |
| Pump output   | l/min       | 50+25             |
| Rear auxiliary hydraulic distributors                           | No. of ways | 6/10              |
| PLATFORM  |             |                   |
| Suspended on silent-block mounts                                |             | •                 |
| Fixed 4-post ROPS   |             | •                 |
| Sunshade roof   |             | 0                 |
| Lateral transmission levers                                     |             | •                 |
| Driver seat with mechanically sprung/air sprung suspension      |             | ●/○               |
| Provision for after-market cab                                  |             | 0                 |
| CRAWLER TRACKS  |             |                   |
| Dry / lubricated track chains                                   |             | ●/○               |
| Pressed steel/cast track guards                                 |             | e/0               |
| Wet rollers and track tensioner wheels                          |             | •                 |
| Track carrier rollers   | No.         | 6/1               |
| Shoes per track/shoe width                                      | No./ mm     | 40/450            |
| Track shoe width  | mm          | 450               |
| DIMENSIONS AND WEIGHTS (for steel tracks)                       |             |                   |
| Max. length with link arms                                      | mm          | 3550              |
| Width   | mm          | 1800              |
| Track   | mm          | 1350              |
| Max height at ROPS  | mm          | 2390              |
| Ground clearance  |             | 210               |
| Wheelbase   | mm          | 1850              |
| Weight without ballast  | kg          | 5260              |
| Weight with bar bandst<br>Weight with maximum permitted ballast | kg          | 6140              |
|   | NY          |                   |

- Not available

## Area dealer

To find out more, visit **same-tractors.com** or talk to you dealer.

