



[ CODENAME ]

# FRUTTETO 80 CLASSIC

STAGE V

FRUTTETO 80 CLASSIC 80 CV  
FRUTTETO 80 CLASSIC 80 CV  
FRUTTETO 80 CLASSIC 80 CV  
FRUTTETO 80 CLASSIC 80 CV

Cab - Platform



**SAME**

# FRUTTETO 80 CLASSIC

## Frutteto 80 Classic

## Frutteto S 80 Classic

## Frutteto V 80 Classic

ENGINE		
Type		FARMotion 35
Emission level		Stage V
Aspiration		Turbo Intercooler
Injection @ pressure	Type	Common Rail@2.000 bar
Cylinder / Displacement	n°/cc	3/2887
Max. power (ECE R120)	kW/hp	55.8/76
Power at rated engine speed (ECE R120)	kW/hp	55.2/75
Max torque @1.500 rpm	Nm	341
Fuel tank capacity (with front lift/PTO)	l	55 (35)
Fuel tanks capacity with additional fuel tank (with front lift/PTO) - Frutteto Classic	l	95 (75)
Fuel tanks capacity with additional fuel tank (with front lift/PTO) - Frutteto S/V Classic	l	85 (65)
TRANSMISSION - MECHANICAL SHUTTLE		
Number of speeds - 5 gears transmission		30+15 (with mechanical splitter) or 45+45 (with HML 3-Powershift steps)
Max. speed - 5 gears transmission	km/h	40 ECO*
TRANSMISSION - POWERSHUTTLE		
Number of speeds - 5 gears transmission		30+15 (with mechanical splitter) or 45+45 (with HML 3-Powershift steps)
Max. speed - 5 gears transmission	km/h	40 ECO*
PTO		
PTO speeds		540/540E or 540/540E/1000
Groundspeed PTO		o
Front PTO 1000		o
LIFT		
Mechanical rear lift		▲
Electronic rear lift		o
Rear lift capacity - Frutteto Classic	kg	2800
Rear lift capacity - Frutteto S/V Classic	kg	2600
Hydraulic right tie rod and stabilisers		o
Front lift (1500 kg)		o
HYDRAULICS		
Open centre hydraulic system (STD)	l/min	54
Open centre hydraulic system with double pump (OPT)	l/min	64
Rear spool valves (STD)	n°	3
Flow regulator		▲
Rear free return		▲
Mid-mounted hydraulic ways - duplicated from rear (OPT)	n° of ways	2/4
Mid-mounted free return		▲
BRAKES		
4 wheel braking		▲
Hydraulic trailer brake		o
FRONT AXLE		
Electrohydraulic engagement for 4WD and Diff.Lock		▲
Auto 4WD		o
Independent steering pump		▲
ACTIVEDRIVE FRONT AXLE (OPT)		
Adaptive-Damping, Active Self-Levelling functions		▲
Anti-Dive, Anti-Roll functions		▲
Differential Traction Control (DTC)		▲
CAB		
4-post cab		▲
Driver seat with pneumatic suspension		▲
Air conditioning		o
4x Halogen working lights		o
Adjustable steering column		o
PLATFORM (Frutteto Classic)		
2-post foldable ROPS		o
Driver seat with mechanical suspension		▲

- ▲ STD
- o OPT
- Not available

\* According to rear tyres size. ECO only for Frutteto Classic and Frutteto S Classic

		<b>Frutteto 80 Classic</b>	
<b>DIMENSIONS</b>			
With front tyre	Size	300/70 R20	
With rear tyre	Size	420/70 R28	
Wheelbase	mm	2011	
Max. length	mm	3680	
Total height - CAB	mm	2396	
Height at bonnet	mm	1453	
Width	mm	1624	
Weight - platform	Kg	2730	
Weight - CAB	Kg	2995	
Total admissible load	Kg	5000	

		<b>Frutteto S 80 Classic</b>	
<b>DIMENSIONS</b>			
With front tyre	Size	280/70 R18	
With rear tyre	Size	380/70 R28	
Wheelbase	mm	2050	
Max. length	mm	3695	
Total height - CAB	mm	2371	
Height at bonnet	mm	1503	
Width	mm	1380	
Weight - CAB	Kg	2850	
Total admissible load	Kg	4600	

		<b>Frutteto V 80 Classic</b>	
<b>DIMENSIONS</b>			
With front tyre	Size	180/95 R16	
With rear tyre	Size	280/85 R24	
Wheelbase	mm	2050	
Max. length	mm	3695	
Total height - CAB	mm	2271	
Height at bonnet	mm	1483	
Width	mm	1166	
Weight - CAB	Kg	2830	
Total admissible load	Kg	4600	



### HYDRAULIC SYSTEM

- 3 rear spool valves with flow regulator and 1 rear free return
- Up to 4 duplicated mid-mounted hydraulic ways
- Single pump with 54 l/min or Double pump with 64 l/min oil flow

### TRANSMISSION

- Mechanical shuttle or PowerShuttle with Stop&Go and Comfort Clutch function
- 30+15 or 45+45 with 3-Powershift steps (HML)
- Max speed: 40 km/h ECO (with 28" rear tyres)

### DRIVING POSITION

- 4-post cab or Platform
- Driver seat with mechanical or pneumatic suspension
- Platform with foldable ROPS available

### ENGINE

- FARMotion 35 engine for high maneuverability
- Compact EAT which does not need additional fluids like AdBlue
- High pressure Common Rail

### AXLES AND BRAKES

- Fixed front axle or ActiveDrive
- True 4-wheel braking
- Auto4WD function available
- Overall width Frutteto Classic: from 1.45 m to 1.65 m
- Overall width Frutteto S Classic: from 1.26 to 1.47 m
- Overall width Frutteto V Classic: from 1.16 to 1.31 m

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.  
Cod. 3089006.3.1.0 - 04/2022

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of  SDF



# SAME