



[CODENAME]

FRUTTETO

STAGE V

Il motore è conforme al regolamento CE n. 1675/2001 e rispetta i requisiti di Stage V.

Il motore è conforme al regolamento CE n. 1675/2001 e rispetta i requisiti di Stage V.

Platform 95 | 105 | 115



SAME

FRUTTETO WITH PLATFORM

		95	105	115
ENGINE				
Type		FARMotion 45		
Emission level		Stage V		
Aspiration		Turbo Intercooler		
Injection @ pressure	Type	Common Rail @ 2000 bar		
Cylinder / Displacement	n°/cc	4/3849		
Max. power (ECE R120)	kW/hp	70/95	78/106	85/116
Power at rated engine speed (ECE R120)	kW/hp	66.4/90	74/101	80.6/110
Max torque @ 1.400 rpm	Nm	389	433	472
Fuel tank capacity	l	82		
AdBlue tank capacity	l	13		
TRANSMISSION - MECHANICAL SHUTTLE				
Number of speeds - 4 gears transmission		12+12 or 24+12 (with mechanical splitter)		
Max. speed - 4 gears transmission	km/h	40		
Number of speeds - 5 gears transmission		15+15 or 30+15 (with mechanical splitter) or 30+30 (with HI-LO 2-Powershift steps)		
Max. speed - 5 gears transmission	km/h	40 ECO*		
PTO				
PTO speeds		540/540E or 540/540E/1000		
Groundspeed PTO		○		
Front PTO and front lift prearrangement		○		
LIFT				
Mechanical rear lift		▲		
Rear lift capacity (STD/OPT)	kg	3130/3940		
Front lift and front PTO prearrangement		○		
HYDRAULICS				
Open centre hydraulic system (STD/OPT)	l/min	48/56		
Open centre hydraulic system with double pump (OPT)	l/min	68		
Rear spool valves (STD/OPT)	n°	2/3		
Flow regulator		○		
Rear free return		▲		
BRAKES				
4 wheel braking		▲		
Hydraulic trailer brake		○		
FRONT AXLE				
Electrohydraulic engagement for 4WD and Diff.Lock		▲		
Independent steering pump		▲		
Front axle with wet disc brakes		▲		
DRIVING POSITION				
Welded platform with tunnel		▲		
2-post foldable safety frame		○		
Suspended on Hydro silent-block		▲		
Driver seat with mechanical suspension		○		
Height adjustment of steering column		○		
Smartphone holder with 2 USB chargers		○		

- ▲ STD
- OPT
- Not available

* According to rear tyres size

		95	105	115
DIMENSIONS				
With front tyre	Size	240/70 R16	240/70 R16	240/70 R16
With rear tyre	Size	380/70 R20	380/70 R20	380/70 R20
Wheelbase	mm	2174	2174	2174
Max. length	mm	3955	3955	3955
Total height - ROPS	mm	2355	2355	2355
Height at bonnet	mm	1351	1351	1351
Height at mudguards	mm	1180	1180	1180
Width	mm	1540	1540	1540
Weight	kg	2650	2650	2650
Total admissible load	kg	5000	5000	5000

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.
Cod. 308.9008.3.1-0 - 07/2022

NEW HYDRAULIC SYSTEM

- 3 rear spool valves with free return
- Flow regulator availability
- Single pump with 48 or 56 l/min or Double pump with 68 l/min oil flow
- Rear lift capacity up to 3940 kg

TRANSMISSION

- From 12+12 up to 30+30 with 2-Powershift steps (Hi-Lo) Mechanical splitter available (24+12 or 30+15)
- Maximum speed of 40 km/h at economy engine revs (with 5-gears transmission)
- Minimum speed of 187 m/h

DRIVING POSITION

- Platform suspended on Hydro Silent-Block
- Two platforms with different mudguard heights
- Adjustable steering column
- Ergonomic spool and lift controls. All controls grouped following colour coding logic

ENGINE

- FARMotion 45 features the highest displacement in the segment
- Max. power up to 116 HP
- Tapered and sloping bonnet gives excellent agility and visibility

AXLES


- Fixed front axle with 100% differential lock as standard
- True 4-wheel braking
- 4WD and diff. lock electro-hydraulically engaged
- Two steering rams for precise steering



SAME

To find out more, visit [same-tractors.com](https://www.same-tractors.com) or talk to your dealer.



SAME is a brand of  SDF