

[CODENAME]

FRUTTETO³ NATURAL

[DISTINGUISHING FEATURES]

PRODUCTIVITY AND RELIABILITY



- The perfect compromise between productivity and reliability. SAME Frutteto³ Natural is the perfect combination of simplicity and strength, a compact multi-functional tractor with power from 55 to 75 Hp, 2WD or 4WD. Thanks to its reduced dimensions and the robustness of its components, the SAME Frutteto³ Natural is ideal both for specialised crops and open field work. The reliable and tested 1000 Series SDF engines ensure long life with low operating costs.

FRUTTETO³ NATURAL: 55 / 65 / 75 / 80.4



SAME

FRUTTETO³ NATURAL

		55	65	75	80.4
ENGINE					
Emissions		Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		SDF1000.3 WT	SDF 1000.3 WT	SDF1000.3 WT1	SDF 1000.4 WT1
Cylinders/Capacity	No./cc	3/3000	3/3000	3/3000	4/4000
Naturally aspirated		-	-	-	-
Turbocharged intake		▲	▲	-	-
Turbo Intercooler intake		-	-	▲	▲
Max. homologated power (ECE R120)	kW/hp	36.8/50	46/62	53/72	55/75
Max. engine speed (rated)	rpm	2,200	2,200	2,200	2,200
Max. torque	Nm	213	240	265	285
Engine control mechanical		▲	▲	▲	▲
Cooling liquid		▲	▲	▲	▲
Under-hood silencer with side exhaust		▲	▲	▲	▲
Fuel tank capacity	litres	65	65	65	65
MECHANICAL GEARBOX					
Synchronised		▲	▲	▲	▲
Number of speeds	n°	8+8	8+8	8+8	8+8
Number of speeds with supercreeper gear	n°	15+15	15+15	15+15	15+15
Minimum/minimum speed with supercreeper gear	km/h	1.77/0.28	1.77/0.28	1.77/0.28	1.77/0.28
Max. speed	km/h	40	40	40	40
Mechanical clutch dry, single		▲	▲	▲	▲
REAR PTO					
Mechanical clutch dry, single		▲	▲	▲	▲
Mechanical engagement		▲	▲	▲	▲
PTO 540		▲	▲	▲	▲
PT.O. 540/540ECO		○	○	○	○
FRONT AND REAR AXLE					
Front wheel drive mechanically engaged (for 4WD versions only)		▲	▲	▲	▲
Mechanically operated differential lock		▲	▲	▲	▲
Steering angle/radius 2WD	degrees/mm	70°/3,390	70°/3,390	70°/3,390	70°/3,390
Steering angle/radius 4WD	degrees/mm	55°/4,680	55°/4,680	55°/4,680	55°/4,680
BRAKES					
Braking system with wet brake discs		▲	▲	▲	▲
Mechanical parking brake		▲	▲	▲	▲
STEERING					
Hydrostatic steering with independent pump		▲	▲	▲	▲
Steering pump flow	l/min	18	18	18	18
HITCH					
Category		II	II	II	II
Rear hitch mechanical		▲	▲	▲	▲
Rear hitch lift capacity	kg	2845	2845	2845	2845
HYDRAULIC SYSTEM					
Pump output (opt)	l/min	42	42	42	42
Open-centre hydraulic system		▲	▲	▲	▲
Mechanical distributor engagement		▲	▲	▲	▲
Rear auxiliary distributors	No. of ways	2 / 4	2 / 4	2 / 4	2 / 4
DRIVING POSITION					
Side control levers		▲	▲	▲	▲
Folding front roll bar		▲	▲	▲	▲
Driver seat with mechanical suspension		▲	▲	▲	▲
Instrumentation analogue		▲	▲	▲	▲
DIMENSIONS AND WEIGHTS					
Standard rear tyres		380/70R24	380/70R24	380/70R24	380/70R24
Width	mm	1538	1538	1538	1538
Wheelbase 4WD	mm	2042	2042	2042	2120
Front track 4WD	mm	1354	1354	1354	1354
Rear track	mm	1221	1221	1221	1221
Max. height with roll bar folded down	mm	2372	2372	2372	2372
Max. height at hood	mm	1468	1468	1468	1468
Weight	kg	2450	2500	2550	2550
Maximum load capacity 4WD	kg	4800	4800	4800	5000

▲ STD ○ OPT - Not available

TECHNICAL DATA

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice. Code 308.8162/4.1-4 - 04/21



SAME

To find out more, visit same-tractors.com or talk to your dealer.



SAME is a brand of SDF