



[ CODENAME ]

# FRUTTETO<sup>3</sup> CLASSIC

STAGE III A



60 - 70 - 80 - 80.4 - 90 - 100



**SAME**

# FRUTTETO<sup>3</sup> CLASSIC

		60	70	80	80.4	90	100
<b>ENGINE</b>							
Emissions		Stage III A	Stage III A	Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		SDF 1000.3 WT	SDF 1000.3 WTI	SDF 1000.3 WTI	SDF 1000.4 WTI	SDF 1000.4 WTI	SDF 1000.4 WTI
Cylinders/Displacement	n°/cc	3/3000	3/3000	3/3000	4/4000	4/4000	4/4000
Turbocharged intake		▲	-	-	-	-	-
Turbo intercooler intake		-	▲	▲	▲	▲	▲
Max. power	kW/HP	45.5/62	53/72	60/82	58.8/80	62.5/85	70/95
Power at rated engine speed	kW/HP	45.5/62	53/72	60/82	55/75	62.5/85	70/95
Max. torque at 1600 rpm	Nm	240	265	310	325	345	373
Electronic engine management		▲	▲	▲	▲	▲	▲
Fuel tank capacity	litres	50	50	50	50	50	50
<b>SHUTTLE</b>							
Synchronised mechanical reverse shuttle		▲	▲	▲	▲	▲	▲
<b>MECHANICAL GEARBOX</b>							
5 speed gearbox		▲	▲	▲	▲	▲	▲
Speeds with underdrive	n°	20+10	20+10	20+10	20+10	20+10	20+10
Speeds with underdrive and supercreeper gear	n°	30+15	30+15	30+15	30+15	30+15	30+15
<b>REAR PTO</b>							
Mechanical engagement		▲	▲	▲	▲	▲	▲
PTO 540		○	○	○	○	○	○
PTO 540/540ECO		▲	▲	▲	▲	▲	▲
PTO 540/540ECO/1000		○	○	○	○	○	○
Ground speed PTO		○	○	○	○	○	○
<b>FRONT AND REAR AXLE</b>							
Four wheel drive mechanically engaged		▲	▲	▲	▲	▲	▲
Differential lock mechanically engaged		▲	▲	▲	▲	▲	▲
<b>BRAKES AND STEERING</b>							
Multi-disc wet brakes on all four wheels		▲	▲	▲	▲	▲	▲
Independent parking brake		▲	▲	▲	▲	▲	▲
Hydraulic trailer braking		○	○	○	○	○	○
Hydrostatic steering with independent pump		▲	▲	▲	▲	▲	▲
Steering angle	degrees	60	60	60	60	60	60
<b>LIFT</b>							
Mechanical rear lift		▲	▲	▲	▲	▲	▲
Rear lifting capacity	kg	2600	2600	2600	3000	3000	3000
<b>HYDRAULIC SYSTEM</b>							
Pump flow	l/min	45	45	45	45	45	45
Rear hydraulic auxiliary spool valves	n° of ways	4/6	4/6	4/6	4/6	4/6	4/6
<b>PLATFORM</b>							
Semi-platform		▲	▲	▲	▲	▲	▲
Digital display		▲	▲	▲	▲	▲	▲
Safety frame		▲	▲	▲	▲	▲	▲
Driver seat with mechanical suspension		▲	▲	▲	▲	▲	▲
<b>DIMENSIONS AND WEIGHTS</b>							
Standard rear tyres		360/70R24"	360/70R24"	380/70R24"	360/70R24"	380/70R24"	380/70R24"
Max. length without rear linkage	mm	3186	3186	3208	3338	3338	3338
Width (min.-max.)	mm	1514-2012	1588-1988	1514-2012	1588-1988	1588-1988	1588-1988
Max. height at ROPS	mm	2228	2250	2250	2380	2380	2380
Ground clearance	mm	270	270	270	270	270	270
Wheelbase	mm	1990	1990	1990	2120	2120	2120
Turning circle	mm	3600	3600	3600	3700	3700	3700
Max. weight with ROPS	kg	2500	2500	2500	2650	2650	650
Max. load capacity	kg	5000	5000	5000	5000	5000	5000

- ▲ STD
- OPT
- Not available

Models and options may vary depending on the market. Please contact your dealer/distributor for more information.

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of SDF

TECHNICAL DATA

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice. 308.9029.3.1-0 - 03/26



**SAME**