



[ CODENAME ]

# FRUTTETO<sup>3</sup> NATURAL

STAGE III A



55 - 65 - 75 - 80.4



**SAME**

# FRUTTETO<sup>3</sup> NATURAL

		55	65	75	80.4
<b>ENGINE</b>					
Emissions		Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		SDF 1000.3 WT	SDF 1000.3 WT	SDF 1000.3 WTI	SDF 1000.4 WTI
Cylinders/Displacement	No./cc	3/3000	3/3000	3/3000	4/4000
Naturally aspirated		-	-	-	-
Turbocharged intake		▲	▲	-	-
Turbo Intercooler intake		-	-	▲	▲
Max. homologated power (ECE R 120)	kW/HP	36.8/50	46/62	53/72	55/75
Max. engine speed (rated)	rpm	2200	2200	2200	2200
Max. torque	Nm	213	240	265	285
Engine control mechanical		▲	▲	▲	▲
Cooling liquid		▲	▲	▲	▲
Under-hood silencer with side exhaust		▲	▲	▲	▲
Fuel tank capacity	litres	65	65	65	65
<b>MECHANICAL GEARBOX</b>					
Synchronised		▲	▲	▲	▲
Number of speeds	n°	8+8	8+8	8+8	8+8
Number of speeds with supercreeper gear	n°	15+15	15+15	15+15	15+15
Minimum/minimum speed with supercreeper gear	km/h	1.77/0.28	1.77/0.28	1.77/0.28	1.77/0.28
Max. speed	km/h	40	40	40	40
Mechanical clutch dry, single		▲	▲	▲	▲
<b>REAR PTO</b>					
Mechanical clutch dry, single		▲	▲	▲	▲
Mechanical engagement		▲	▲	▲	▲
PTO 540		▲	▲	▲	▲
PTO 540/540ECO		○	○	○	○
<b>FRONT AND REAR AXLE</b>					
Front wheel drive mechanically engaged (for 4WD versions only)		▲	▲	▲	▲
Mechanically operated differential lock		▲	▲	▲	▲
Steering angle/radius 2WD	degrees/mm	70/3390	70/3390	70/3390	70/3390
Steering angle/radius 4WD	degrees/mm	55/4680	55/4680	55/4680	55/4680
<b>BRAKES</b>					
Braking system with wet brake discs		▲	▲	▲	▲
Mechanical parking brake		▲	▲	▲	▲
<b>STEERING</b>					
Hydrostatic steering with independent pump		▲	▲	▲	▲
Steering pump flow	l/min	18	18	18	18
<b>HITCH</b>					
Category		II	II	II	II
Rear hitch mechanical		▲	▲	▲	▲
Rear hitch lift capacity	kg	2845	2845	2845	2845
<b>HYDRAULIC SYSTEM</b>					
Pump output (opt)	l/min	42	42	42	42
Open-centre hydraulic system		▲	▲	▲	▲
Mechanical distributor engagement		▲	▲	▲	▲
Rear auxiliary distributors	N° of ways	2/4	2/4	2/4	2/4
<b>DRIVING POSITION</b>					
Side control levers		▲	▲	▲	▲
Folding front roll bar		▲	▲	▲	▲
Driver seat with mechanical suspension		▲	▲	▲	▲
Instrumentation analogue		▲	▲	▲	▲
<b>DIMENSIONS AND WEIGHTS</b>					
Standard rear tyres		380/70R24	380/70R24	380/70R24	380/70R24
Width	mm	1538	1538	1538	1538
Wheelbase 4WD	mm	2042	2042	2042	2120
Front track 4WD	mm	1354	1354	1354	1354
Rear track	mm	1221	1221	1221	1221
Max. height with roll bar folded down	mm	2372	2372	2372	2372
Max. height at hood	mm	1468	1468	1468	1468
Weight	kg	2450	2500	2550	2550
Maximum load capacity 4WD	kg	4800	4800	4800	5000

- ▲ STD
- OPT
- Not available

Models and options may vary depending on the market. Please contact your dealer/distributor for more information.

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of SDF

TECHNICAL DATA

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.  
308.90300.3.1-0 - 03/26



**SAME**