



[ CODENAME ]

# TIGER COMPACT

STAGE III A



46 - 50 - 55 - 60



**SAME**

# TIGER COMPACT

		46	50	55	60
<b>ENGINE</b>					
Emissions		Stage III A	Stage III A	Stage III A	Stage III A
Manufacturer		Simpson	SDF	SDF	SDF
Cylinders/Capacity	n°/cc	3/2700	3/3000	3/3000	3/3000
Aspiration		Natural	Natural	Turbo Intercooler	Turbo Intercooler
Max. & Rated power (ECE R120)	kW/HP	33/45	36.8/50	40.4/55	44.1/60
Rated engine speed	rpm	2200	2200	2200	2200
Max. torque	Nm	180	184	201	221
Mechanical engine control		▲	▲	▲	▲
Cooling liquid		▲	▲	▲	▲
Under-hood silencer with vertical exhaust		▲	▲	▲	▲
Fuel tank capacity	litres	55	55	55	55
<b>TRANSMISSION 1</b>					
Synchronised		○	○	○	○
Number of speed (with creeper)	n°	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)	8+2 (12+3)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		▲	▲	▲	▲
Waterproof seals		▲	▲	▲	▲
<b>TRANSMISSION 2</b>					
Synchronised		▲	▲	▲	▲
Number of speed (with creeper)	n°	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)	8+8 (12+12)
Minimum speed with reduction gear	km/h	0.5	0.5	0.5	0.5
Max. speed	km/h	34	34	34	34
Mechanical dry clutch		▲	▲	▲	▲
Waterproof seals		▲	▲	▲	▲
<b>REAR PTO</b>					
Mechanical dry clutch		▲	▲	▲	▲
Mechanical engagement		▲	▲	▲	▲
PTO 540 / 540-540ECO / 540-1000		▲ / ○ / ○	▲ / ○ / ○	▲ / ○ / ○	▲ / ○ / ○
PTO 540 + reverse PTO		○	○	○	○
<b>FRONT AND REAR AXLE</b>					
Front wheel drive mechanically engaged (only 4WD)		▲	▲	▲	▲
Mechanically operated differential lock (rear/front)		▲/-	▲/-	▲/-	▲/-
Steering angle (2WD/4WD)	degrees	55/51	55/51	55/51	55/51
<b>BRAKES</b>					
Girling braking system		▲	▲	▲	▲
Mechanical parking brake		▲	▲	▲	▲
<b>STEERING</b>					
Hydrostatic steering with independent pump		▲	▲	▲	▲
<b>HITCH</b>					
Category		II	II	II	II
Mechanical rear hitch with Easy Lift system		▲	▲	▲	▲
Rear hitch lift capacity	kg	1250	1600	1600	1600
<b>HYDRAULIC SYSTEM</b>					
Pump output (STD)	l/min	27	31	31	31
Rear hydraulic auxiliary valves	n° of ways	2/4	2/4	2/4	2/4
<b>DRIVING POSITION</b>					
Side control levers		▲	▲	▲	▲
2 post ROPS		○	○	○	○
Driver seat with mechanical suspension		○	○	○	○
<b>DIMENSIONS AND WEIGHTS</b>					
Rear tyres		16.9-28"	16.9-28"	16.9-28"	16.9-28"
Max. length	mm	3550	3550	3550	3550
Width (min.-max.)	mm	1800-1840	1800-1840	1800-1840	1800-1840
Wheelbase (4WD/2WD)	mm	1950/1920	1950/1920	1950/1920	1950/1920
Front track (4WD/2WD)	mm	1488/1462	1488/1462	1488/1462	1488/1462
Rear track	mm	1440	1440	1440	1440
Max. height at steering	mm	1634	1634	1634	1634
Weight with ROPS (4WD/2WD)	kg	2500/2100	2500/2100	2500/2100	2500/2100

- ▲ STD
- OPT
- Not available

Models and options may vary depending on the market. Please contact your dealer/distributor for more information.

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice. 308.9033.3.1-0 - 03/26°

**TECHNICAL DATA**



**SAME**

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of SDF